



**Specifications Ledvance LED  
Downlight Comfort Opal White  
30W/25W/20W  
3600lm/3000lm/2400lm 100D -  
930-940 CCT | Cutout 200mm - IP44 -  
Best Colour Rendering**

[View Product](#)

## General Information

|                      |                                      |
|----------------------|--------------------------------------|
| SKU                  | 254946                               |
| EAN                  | 4099854490989                        |
| Manufacturer Code    | 4099854490989                        |
| Brand                | Ledvance                             |
| Manufacturer Name    | DL CMFT D200 P 30W MS 940 OP WT LEDV |
| Budgetlight warranty | 5 Years                              |
| Average Lifetime (h) | 100000                               |

## Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tiltable                    | No                |
| Technology                  | LED Integrated    |
| Replaces (Watt)             | 2x26              |
| Wattage                     | 30W               |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 930 Warm White    |
| Colour temperature (Kelvin) | 3000 Warm White   |
| Colour Rendering (Ra)       | 90-99             |

|                       |                          |
|-----------------------|--------------------------|
| Colour of Light       | White                    |
| Light colour options  | Single Color             |
| Beam Angle (degree)   | 100                      |
| Luminous Flux (Lumen) | 3600lm                   |
| Lumen per watt        | 120                      |
| Power factor          | >0.90                    |
| Unified Glare Rating  | < 23 - for general areas |
| Optical Cover         | Opal                     |
| Product Type Category | LED Downlight            |

## Fixture Information

|                        |                        |
|------------------------|------------------------|
| Mounting Method        | Recessed               |
| Cut out (mm)           | 200                    |
| IP-rating              | IP44                   |
| Impact Protection (IK) | IK03 - 0.35 joule      |
| Operating Temperature  | -20 to +40             |
| Housing                | Aluminium              |
| Colour of the Fixture  | White                  |
| Fixture Connection     | PI [Push-in connector] |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 59  |
| Diameter (mm) | 215 |

**Sensor Information**  Guaranteed **budget prices**  Up to **7 years warranty**

Type of sensor

 **Easy** return process

No Sensor



Long-life **LED solutions**